Declaration of Performance according to Regulation (EU) 305/2011

No. POV-HOX011/2013

1) Unique identification code of the product-type:

ECKA 67/45/51 h

2) Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4): H19-001, H19-300, h19-600, h19-650, h19-700, h19-750

Fireplace stoves burning wood made by Hoxter a.s. are designed for heating and additional heating of residential and social rooms, i.e. standard environment without the explosion hazard and the presence of volatile substances. The fireplace stoves are designed for interrupted operation.

Basic technical parameters

Туре	Main dimensions (mm)			Nominal	Fuel	Diameter of	Operational
	Height	Width	Depth	power output (kW)	consumption - wood (kg/hour)	the uptake (mm)	draught (Pa)
ECKA 67/45/51 Lh	1339	826	607	12,0	3,5	180	12
ECKA 67/45/51 Rh	1339	826	607	12,0	3,5	180	12
ECKA 67/45/51 L	1176	732	527	12,0	3,5	180	12
ECKA 67/45/51 L	1176	732	527	12,0	3,5	180	12

3) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Room heater burning solid fuel *without* hot water supply Appliances are determined for intermittent operation. According to (ČSN) EN 13229/A2 Table 1 - "Sorting of appliances" it concerns products 1b.

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):

Hoxter a.s. Mlýnská 326/13 602 00, Brno Czech Republic IČ: 28359542

Tel.: +420 518 777 701 E-mail: info@hoxter.eu

- 5) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): N/A
- 6) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 (Annex V, Clause 1.4 of Regulation 305/2011 of the European Parliament and of the Council of 9 March 2011)

7) The Declaration of Performance concerning a construction product covered by a harmonized standard:

(ČSN) EN 13229:2001 /A2:2004/AC:2007 The assessment acc. to System 3 has been carried out by Strojírenský zkušební ústav, s.p., Hudcova 424/56b, 621 00 Brno, Notified Body 1015, which issued the Report on Initial Type Testing 30-11498-2 of 2012-06-18.

8) Declared performance:

Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007 Performance		
Essential characteristics			
Fir	e safety		
Reaction to fire	A1		
Distance to combustible materials	Minimum distances, in mm		
	rear = 200		
	sides = 150		
	ceiling = 1200		
	front = 800		
Risk of burning fuel falling out	Pass		
Emission of combustion products	CO[0.0768 %]		
Surface temperature	Pass		
Electrical safety	Pass		
Cleanability	Pass		
Maximum operating pressure	-		
Flue gas temperature at nominal	T [269 °C]		
heat output			
Mechanical resistance (to carry a	NPD		
chimney/flue)			
Therr	nal output		
Nominal heat output	12,0 kW		
Room heating output	11,8 kW		
Water heating output	-		
Energy efficiency	[81,69 %]		

9) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing. Petr Veselský Technical Director

In Kuřim on 1. 7. 2013

HOXTER, a.s. (2)
sídlo Mlýnská 326/13, Brno 502 00
IČ: 283 59 542, DIČ:CZ28359542
signature