Declaration of Performance according to Regulation (EU) 305/2011

No. **POV-HOX066/2020**

1. Unique identification code of the product-type:

ECKA 80/35/50Sh

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4): h50-001L, h50-001R

Fireplace stoves burning wood made by Hoxter a.s. are designed for heating and additional heating of residential and social rooms, i.e. standard environment without the explosion hazard and the presence of volatile substances. The fireplace stoves are designed for interrupted operation.

Basic technical parameters

Type	Main dimensions (mm)			Nominal power	Fuel consumption	Diameter of the	Operational draught
1,400	Height	Width	Depth	output (kW)	- wood (kg/hour)	uptake (mm)	(Pa)
ECKA 80/35/50SLh	1300	906	467	10	2,9	180	12
ECKA 80/35/50SRh	1042	629	398	10	2,9	180	12

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Room heater burning solid fuel. Appliances are determined for intermittent operation. According to (ČSN) EN 13229/A2 Table 1 - "Sorting of appliances" it concerns products 1b.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5):

HOXTER, a.s. Jinacovice 512 664 34 Jinacovice Czech Republic IČ: 28359542

Tel.: +420 518 777 701 E-mail: info@hoxter.eu

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 (Annex V, Clause 1.4 of Regulation 305/2011 of the European Parliament and of the Council of 9 March 2011)

7. The Declaration of Performance concerning a construction product covered by a harmonized standard:

(ČSN) EN 13229:2001 /A2:2004/AC:2007 The assessment acc. to System 3 has been carried out by Strojírenský zkušební ústav, s.p., Hudcova 424/56b, 621 00 Brno, Notified Body 1015, which issued the Report on Initial Type Testing 30-14928/2/T of 2020-10-27.

8. Declared performance:

Harmonized technical specification	EN 13229:2001/A2:2004/AC:2007			
Essential characteristics	Performance			
Fire safety				
Reaction to fire	A1			
Distance to combustible materials	Minimum distances, in mm rear = 200 sides = 400			
Distance to compustible materials	ceiling = 800 front = 800			
Risk of burning fuel falling out	Pass			
Emission of combustion products	CO[0.0837 %]			
Surface temperature	Pass			
Electrical safety	NPD*			
Cleanability	Pass			
Maximum operating pressure	NPD*			
Flue gas temperature at nominal heat output	T [209 °C]			
Mechanical resistance (to carry a chimney/flue)	NPD*			
Thermal output				
Nominal heat output	10 kW			
Room heating output	10,4 kW			
Water heating output	-			
Energy efficiency	[85,6 %]			

^{*) &}quot;NPD" (No Performance Determined),

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing. Petr Veselský
Technical Director

In Jinacovice on 30.10.2020

E HOXTER, a.s.

Jinačovice 512, CZ - 664 34 Jinačovice
1č. 283 59 542, DIČ: CZ28359542

signature